

AMENDMENT TO THE DRAWINGS:

The attached sheet of Drawings includes changes to Figs. 7 and 8. This sheet, which includes Figs. 7 and 8, replaces the original sheets including Figs. 7 and 8.

Attachment: one (1) Replacement Sheet.

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

Claims 1-9 (canceled).

Claim 10 (new): A lamination-type resistance element comprising:

a laminated sinter having a plurality of ceramic resistance layers and a plurality of internal electrodes laminated therein; and

a first external electrode and a second external electrode provided on the outer surface of the laminated sinter; wherein

the plurality of internal electrodes includes a plurality of internal electrodes of a first group and a plurality of internal electrodes of a second group;

each of the plurality of internal electrodes of the first group includes a resistance unit in which at least two internal electrodes are disposed so as to face each other through one of the ceramic resistance layers, a first end of the resistance unit is electrically connected to the first external electrode, and a second end is electrically connected to the second external electrode; and

each of the internal electrodes of the second group includes a plurality of pairs of internal electrodes in which a first end of one electrode faces a first end of the other electrode with a gap therebetween on the same plane inside the laminated sinter, one internal electrode in each pair is electrically connected to the first external electrode, and the other is electrically connected to the second external electrode.

Claim 11 (new): The lamination-type resistance element as claimed in claim 10, wherein the plurality of gaps of the second group is arranged so as to lie on top of one another in the lamination direction in the laminated sinter.

Claim 12 (new): The lamination-type resistance element as claimed in claim 10, wherein each of the internal electrodes of the first group includes a first divided internal electrode electrically connected to the first external electrode and a second divided internal electrode electrically connected to the second external electrode, and a first end of the first divided internal electrode and a first end of the second divided internal electrode face each other with a gap therebetween on the same plane.

Claim 13 (new): The lamination-type resistance element as claimed in claim 12, wherein a topmost gap of the first group is aligned with a bottommost gap of the second group.

Claim 14 (new): The lamination-type resistance element as claimed in claim 12, wherein a plurality of pairs of first and second divided internal electrodes is laminated and the gaps in neighboring pairs of electrodes in the lamination direction are arranged at different locations when seen from one side in the lamination direction.

Claim 15 (new): The lamination-type resistance element as claimed in claim 12, wherein the first group includes a no-connection-type internal electrode disposed on top of the first and second divided internal electrodes through a ceramic resistance layer.

Claim 16 (new): The lamination-type resistance element as claimed in claim 10, wherein each of the internal electrodes of the first group each includes a first internal electrode electrically connected to the first external electrode and a second internal electrode electrically connected to the second external electrode, and the first and second internal electrodes are disposed so as to lie on top of one another with a ceramic layer disposed therebetween.

Claim 17 (new): A lamination-type resistance element comprising:

a laminated sinter having a plurality of ceramic resistance layers and a plurality of internal electrodes laminated therein; and

a first external electrode and a second external electrode provided on the outer surface of the laminated sinter; wherein

the internal electrodes include internal electrodes of a first group and internal electrodes of a second group;

each of the internal electrodes of the first group includes a first internal electrode and a second internal electrode in which a first end of one electrode is arranged so as to face a first end of the other electrode with a gap therebetween on the same plane inside the laminated sinter and the second ends are connected to the first external electrode and the second external electrode, respectively, and neighboring gaps between the first and second internal electrodes in the lamination direction of the laminated sinter are arranged at different locations when seen from the lamination direction of the laminated sinter; and

each of the internal electrodes of the second group includes a third internal electrode and a fourth internal electrode in which a first end of the third internal electrode faces a first end of the fourth internal electrode other with a gap therebetween

on the same plane inside the laminated sinter, and second ends are connected to the first external electrode and the second external electrode, respectively, and the gaps between the third internal electrodes and fourth internal electrodes are at the same location along the lamination direction of the laminated sinter.

Claim 18 (new): A lamination-type resistance element comprising:

a laminated sinter having a plurality of ceramic resistance layers and a plurality of internal electrodes laminated therein; and

a first external electrode and a second external electrode provided on the outer surface of the laminated sinter; wherein

the internal electrodes include internal electrodes of a first group and internal electrodes of a second group;

each of the internal electrodes of the first group includes a first internal electrode and a second internal electrode in which a first end of the first internal electrode is arranged so as to face a first end of the second internal electrode with a gap therebetween on the same plane inside the laminated sinter, and second ends are connected to the first external electrode and the second external electrode, respectively, and a no-connection-type internal electrode which is arranged so as to lie on top of the first internal electrode and the second internal electrode through the ceramic resistance layer in the lamination direction of the laminated sinter and which is not connected to the first and second external electrodes; and

each of the internal electrodes of the second group includes a third internal electrode and a fourth internal electrode in which a first end of the third internal electrode faces a first end of the fourth internal electrode with a gap therebetween on the same plane inside the laminated sinter, and second ends are connected to the first

external electrode and the second external electrode, respectively, and the gaps between the third internal electrodes and fourth internal electrodes are at the same location along the lamination direction of the laminated sinter.

Claim 19 (new): A lamination-type resistance element comprising:

a laminated sinter having a plurality of ceramic resistance layers and a plurality of internal electrodes laminated therein; and

a first external electrode and a second external electrode provided on the outer surface of the laminated sinter; wherein

the internal electrodes include internal electrodes of a first group and internal electrodes of a second group;

each of the internal electrodes of the first group includes a first internal electrode connected to the first external electrode and a second internal electrode connected to the second external electrode which face each other through the ceramic resistance layer; and

each of the internal electrodes of the second group includes a third internal electrode and a fourth internal electrode in which a first end of third internal electrode faces a first end of the fourth internal electrode with a gap therebetween on the same plane inside the laminated sinter, and second ends are connected to the first external electrode and the second external electrode, respectively, and the gaps between the third internal electrodes and fourth internal electrodes are at the same location along the lamination direction of the laminated sinter.